

■ TYPE I SAFETY STORAGE CANS



No. 4615C



No. 3615C

Protectoseal Type I Safety Storage Cans feature rugged, heavy duty, industrial design and construction for safe, in-plant storage and transport of flammables. Made of high quality 22-gauge steel. Cans are FM Approved and UL Listed and exceed OSHA and NFPA requirements. Features include a locking flash arrester that prevents ignition of vapors within the container due to external flames. The wide opening spout allows fast, easy filling and pouring, while the spring-operated, self-closing cap opens to relieve internal vapor pressure before pouring. Shock rim and raised bottom provide extra strength and protection against damage. Leak resistant gasket in spout cap.

Type I cans are offered in two great designs in 1 gallon to 5 gallon capacities. An ergonomically designed cast handle for convenient one hand pouring and the more economically priced tubular handle.

Color-coded cans are available for the storage of Kerosene and Diesel Fuel. The industry standards of BLUE for Kerosene and YELLOW for Diesel Fuel are used.

ERGONOMICALLY DESIGNED HANDLE

Capacity (gals.)	Height	O.D.	Listing	RED Cat. No.	BLUE Cat. No.	YELLOW Cat. No.
1	12"	9"	FM,UL,ULC	PSS100 ¹	N/A	N/A
2	16¼"	9"	FM,UL,ULC	PSS102 ¹	N/A	N/A
3	15½"	12"	FM,UL,ULC	PSS103 ¹	N/A	N/A
5	19½"	12"	FM,UL,ULC	4615C	N/A	N/A

ECONOMICALLY DESIGNED HANDLE

Capacity (gals.)	Height	O.D.	Listing	RED Cat. No.	BLUE Cat. No.	YELLOW Cat. No.
1	10¼"	9"	FM, UL	PSC1000	PSC1000B	PSC1000Y
2	15"	9"	FM, UL	3612	3612K	PSC1020Y
3	14¼"	12"	FM, UL	PSC1030	3613K	3613Y
5	18"	12"	FM, UL	PSC1050	PSC1050B	PSC1050Y

¹ Outsourced product distributed by Protectoseal. Exempt from ISO System Review.

■ NO. 4615CS FUEL REMOVAL SAFETY SIPHON CAN

Unique can was specially designed to safely pump or siphon unwanted fuel from gas powered equipment such as lawn mowers, chain saws, snowmobiles, etc. Rugged can includes perforated metal flash arresters at all openings and the hand-operated pump controls flow of gasoline from the apparatus into the container.

Capacity (gals.)	Height	O.D.	Cat. No.
5	19⅝"	12"	4615CS ¹

¹ Outsourced product distributed by Protectoseal. Exempt from ISO System Review.



SAFETY STORAGE & DISPENSING CANS

■ TYPE II SAFETY DISPENSING CANS



Protectoseal Type II Safety Dispensing Cans are specifically designed for the convenient dispensing of flammable liquids into vessels, cans or tanks which have a small receiving opening. Type II cans are commonly identified by their separate fill and pouring openings. They feature a flexible metal dispensing hose that eliminates the need for a funnel and provides a bonding path to prevent static sparks. Pouring mechanism also has an automatic integral vacuum relief vent that protects container from implosion. Made of high quality terne plate. Cans are FM Approved and UL Listed and exceed OSHA and NFPA requirements. Type II cans have perforated-metal flash arresters at both fill opening and the base of pouring spout for protection of contents against external ignition sources. Shock rim and raised bottom provide extra strength and protection against damage. Leak resistant gasket in fill cap. High gloss RED enamel finish.

Color-coded cans are available for the storage of Kerosene and Diesel Fuel. The industry standards of BLUE for Kerosene and YELLOW for Diesel Fuel are used.

Capacity (gals.)	Height	O.D.	Hose O.D./Length	Listing	RED Cat. No.	BLUE Cat. No.	YELLOW Cat. No.	Replacement Hose Assy.
1	12"	9"	3/4" / 6"	FM,UL,ULC	PSP200 ¹	N/A	N/A	PSP200-90 ¹
2	16 1/4"	9"	3/4" / 6"	FM,UL,ULC	PSP202 ¹	N/A	N/A	PSP200-90 ¹
3	15 1/2"	12"	3/4" / 9"	FM,UL,ULC	PSP203 ¹	PSP203B ¹	PSP203Y ¹	PSP205-90 ¹
5	19 1/2"	12"	3/4" / 9"	FM,UL,ULC	PSP205 ¹	PSP205B	PSP205Y ¹	PSP205-90 ¹

¹ Outsourced product distributed by Protectoseal. Exempt from ISO System Review.

■ SAFETY CAN W/ SELF-CLOSING BOTTOM FAUCET

Rugged steel funnels have a spring clip for quick easy attachment to Protectoseal Type I Safety Designed for bench or elevated shelf use, this safety can features a self-closing, rigid brass faucet and is well suited to dispense liquids into smaller containers without tipping or handling the can.

Capacity (gals.)	Height	O.D.	Cat. No.
5	19 1/5"	12"	F-1050 ¹

¹ Outsourced product distributed by Protectoseal. Exempt from ISO System Review.



No. F-1050